

# DSP-10

## Genset Multi-Function Display Module

### Features

- First and only Multi-function Display Module specially designed for generator set
- Three sets four Digits High illumination LED Suitable for Outdoor use
- Microprocessor Based Design
- Full Phase AC Voltage RMS value Display
- Full Phase with Load RMS value Display
- AC Input Frequency Display
- DC Supply Voltage Display
- Engine Operating Time Display
- All values can be programmed according to user's actual demand to be cyclic displayed
- Compact, Anti-shock, Easy installation
- DIN rail terminal for easy connection
- Four adjustable Voltage and Current Push Buttons
- Five Dip Switches For Specification Setting



**DSP-10**  
www.kutai.com.tw

### Specifications

<b>DC Supply</b>	DC Voltage 9~36 VDC (12V , 24V)	<b>Rated CT Capacity</b>	Above 2.5 VA
<b>Alternator Input Range</b>	AC Voltage 10~500 VAC	<b>CT Secondary Ratio</b>	5A
	Frequency 50/60 Hz	<b>Max. CT Rated</b>	3000A / 5A
<b>Power Consumption</b>	2 watt		

### Environment

<b>Operating Temperature</b>	-20~70 °C
<b>Storage Temperature</b>	-35~85 °C
<b>Relative Humidity</b>	Maximum 90%

### Physical Specification

<b>Panel Cut-Out</b>	66.0 x 66.0 ±0.5 mm
<b>Dimensions</b>	72.0 (H) x 72.0 (W) x 50.0 (D) mm
<b>Weight</b>	200 g ±2%

### Mechanical Specifications (Unit : mm)

